

Nextiva S2800e IP PTZ Dome Camera

V-UCP Universal Ceiling

VERINT.

VIDEO INTELLIGENCE SOLUTIONS™



2009 Verint Systems Inc. All Rights Reserved Worldwide.

Unauthorized use, duplication, or modification of this document in whole or in part without the written consent of Verint Systems Inc. is strictly prohibited. By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice. Features listed in this document are subject to change.

Verint Systems Inc. does not warrant, guarantee or make any representation regarding the use or the results of the use of the information, links, tools, and materials in terms of the accuracy, reliability, quality, validity, stability, completeness, currentness, or otherwise of its content or products. The entire risk as to the use, results and performance of information, links, tools and materials provided or referenced herein is assumed by the user. Verint Systems Inc. shall not be liable for damages resulting from the use, misuse or unlawful use of the information, links, tools, and materials contained or referenced herein.

The Verint Systems Inc. products are protected by one or more of the following U.S., European or International Patents: USPN 5,659,768; USPN 5,689,442; USPN 5,790,798; USPN 6,278,978; USPN 6,370,574; USPN 6,404,857; USPN 6,510,220; USPN 6,724,887; USPN 6,751,297; USPN 6,757,361; USPN 6,782,093; USPN 6,952,732; USPN 6,959,078; USPN 6,959,405; USPN 7,047,296; USPN 7,149,788; USPN 7,155,399; USPN 7,203,285; USPN 7,216,162; USPN 7,219,138; USPN 7,254,546; USPN 7,281,173; USPN 7,284,049; USPN 7,325,190; USPN 7,424,715; USPN 7,466,816; USPN 7,478,051; USPN RE40,634; and other provisional rights from one or more of the following Published US Patent Applications: US 11/394,408; US 11/771,499; US 11/396,514; US 11/772,440; US 11/565,943; US 11/565,946; US 11/565,948; US 11/540,739; US 11/540,086; US 11/541,313; US 11/541,252; US 11/540,282; US 11/529,947; US 11/540,785; US 11/540,736; US 11/540,904; US 11/540,353; US 11/608,340; US 11/608,350; US 11/608,358; US 11/567,808; US 11/692,983; US 11/693,933; US 11/693,923; US 11/693,828; US 11/567,852; US 11/608,440; US 12/015,621; US 11/540,322; US 11/924,201; US 11/616,490; US 11/621,134; US 11/752,458; US 11/712,933; US 11/824,980; US 11/729,185; US 11/804,748; US 11/831,260; US 11/395,992; US 11/359,319; US 11/359,195; US 11/359,357; US 10/832,509; US 11/742,733; US 11/831,257; US 11/831,250; US 11/691,530; US 11/479,267; US 11/529,942; US 11/768,349; US 11/540,281; US 10/633,357; US 11/693,899; US 11/479,056; US 11/529,132; US 11/540,320; US 11/037,604; US 11/529,842; US 11/540,171; US 11/478,714; US 11/529,946; US 11/868,656; US 11/776,659; US 11/090,638; US 11/410,004; US 10/771,315; US 10/771,409; US 11/540,900; US 11/528,267; US 12/118,781; and other U.S. and International Patents and Patents Pending.

VERINT, the VERINT logo, ACTIONABLE INTELLIGENCE, POWERING ACTIONABLE INTELLIGENCE, WITNESS ACTIONABLE SOLUTIONS, STAR-GATE, RELIANT, VANTAGE, X-TRACT, NEXTIVA, ULTRA, AUDIOLOG, WITNESS, the WITNESS logo, IMPACT 360, the IMPACT 360 logo, IMPROVE EVERYTHING, EQUALITY, CONTACTSTORE, and CLICK2STAFF are trademarks or registered trademarks of Verint Systems Inc. or its subsidiaries. Other trademarks mentioned are the property of their respective owners.

V-UCP Universal Ceiling Panel

Nextiva® S2800e IP PTZ Dome Camera System

- Convenient mounting for Nextiva S2800e IP PTZ in-ceiling version
- Color coordinated finish for ceiling and camera dome system
- Provides ultimate Nextiva S2800e



The V-UCP Universal Ceiling Panel is designed to mount the Nextiva S2800e IP PTZ Dome Camera System In-Ceiling version. It is a 24 in. (610 mm) x 24 in. (610 mm) x 16 GA. (0.060 in., 1.5 mm) white color painted panel constructed of steel. It is suitable for indoor installations only. The Nextiva S2800e is pushed up through the panel's cutout and secured with its built-in hardware. This panel can be used in any dropped ceiling installation where the standard 2 ft. x 2 ft. grid is installed.

Technical Information

Application:	Indoor, specifically designed for in-ceiling Nextiva S2800e.
Mounting Surface:	24 in. (610 mm) x 24 in. (610 mm) dropped ceiling grid.
Dimensions:	See Figure. Length (L): 23.75 in. (603 mm). Width (W): 23.75 in. (603 mm).
Thickness:	0.060 in. (1.5 mm).
Weight:	8.5 lb (3.9 kg).
Construction:	Sheet steel.
Finish/Color:	Painted white.
Shipping Dimensions:	Length: 24.5 in. (622 mm). Width: 24.5 in. (622 mm). Height: 1.25 in. (31.75 mm).
Shipping Weight:	10 lb (4.5 kg).
Shipping Volume:	0.43 ft ³ (0.012 m ³).

ENVIRONMENTAL

Storage Temperature Range: -40 to 150° F (-40 to 60° C).

Storage Humidity Range: 0 to 90% relative, non-condensing.

