

Nextiva S2800e IP PTZ Dome Camera

V-UPM-1 Outdoor Parapet Mount

VERINT.

VIDEO INTELLIGENCE SOLUTIONS™



2009 Verint Systems Inc. All Rights Reserved Worldwide.

Unauthorized use, duplication, or modification of this document in whole or in part without the written consent of Verint Systems Inc. is strictly prohibited. By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice. Features listed in this document are subject to change.

Verint Systems Inc. does not warrant, guarantee or make any representation regarding the use or the results of the use of the information, links, tools, and materials in terms of the accuracy, reliability, quality, validity, stability, completeness, currentness, or otherwise of its content or products. The entire risk as to the use, results and performance of information, links, tools and materials provided or referenced herein is assumed by the user. Verint Systems Inc. shall not be liable for damages resulting from the use, misuse or unlawful use of the information, links, tools, and materials contained or referenced herein.

The Verint Systems Inc. products are protected by one or more of the following U.S., European or International Patents: USPN 5,659,768; USPN 5,689,442; USPN 5,790,798; USPN 6,278,978; USPN 6,370,574; USPN 6,404,857; USPN 6,510,220; USPN 6,724,887; USPN 6,751,297; USPN 6,757,361; USPN 6,782,093; USPN 6,952,732; USPN 6,959,078; USPN 6,959,405; USPN 7,047,296; USPN 7,149,788; USPN 7,155,399; USPN 7,203,285; USPN 7,216,162; USPN 7,219,138; USPN 7,254,546; USPN 7,281,173; USPN 7,284,049; USPN 7,325,190; USPN 7,424,715; USPN 7,466,816; USPN 7,478,051; USPN RE40,634; and other provisional rights from one or more of the following Published US Patent Applications: US 11/394,408; US 11/771,499; US 11/396,514; US 11/772,440; US 11/565,943; US 11/565,946; US 11/565,948; US 11/540,739; US 11/540,086; US 11/541,313; US 11/541,252; US 11/540,282; US 11/529,947; US 11/540,785; US 11/540,736; US 11/540,904; US 11/540,353; US 11/608,340; US 11/608,350; US 11/608,358; US 11/567,808; US 11/692,983; US 11/693,933; US 11/693,923; US 11/693,828; US 11/567,852; US 11/608,440; US 12/015,621; US 11/540,322; US 11/924,201; US 11/616,490; US 11/621,134; US 11/752,458; US 11/712,933; US 11/824,980; US 11/729,185; US 11/804,748; US 11/831,260; US 11/395,992; US 11/359,319; US 11/359,195; US 11/359,357; US 10/832,509; US 11/742,733; US 11/831,257; US 11/831,250; US 11/691,530; US 11/479,267; US 11/529,942; US 11/768,349; US 11/540,281; US 10/633,357; US 11/693,899; US 11/479,056; US 11/529,132; US 11/540,320; US 11/037,604; US 11/529,842; US 11/540,171; US 11/478,714; US 11/529,946; US 11/868,656; US 11/776,659; US 11/090,638; US 11/410,004; US 10/771,315; US 10/771,409; US 11/540,900; US 11/528,267; US 12/118,781; and other U.S. and International Patents and Patents Pending.

VERINT, the VERINT logo, ACTIONABLE INTELLIGENCE, POWERING ACTIONABLE INTELLIGENCE, WITNESS ACTIONABLE SOLUTIONS, STAR-GATE, RELIANT, VANTAGE, X-TRACT, NEXTIVA, ULTRA, AUDIOLOG, WITNESS, the WITNESS logo, IMPACT 360, the IMPACT 360 logo, IMPROVE EVERYTHING, EQUALITY, CONTACTSTORE, and CLICK2STAFF are trademarks or registered trademarks of Verint Systems Inc. or its subsidiaries. Other trademarks mentioned are the property of their respective owners.

V-UPM-1 Outdoor Parapet Mount for Nextiva® S2800e IP PTZ Dome Camera



- Designed specifically for parapet mounting of Nextiva S2800e Camera Dome System
- Allows convenient cabling for ease of installation
- Easy serviceability

The V-UPM-1 parapet mount is a heavy-duty unit designed specifically for mounting Nextiva S2800e Camera Dome Systems from the inside surface of a roof parapet or similar structure. The V-UPM-1 has a maximum load rating of 40 pounds (18 kg) and provides a sturdy installation capable of withstanding extreme weather conditions.

The V-UPM-1 allows the mounted equipment to be swiveled in toward the roof to provide access for convenient rooftop servicing or adjustment. All cabling is conveniently routed through the mount.

Technical Information

MECHANICAL

Mounting Flange Thread: 1-1/2 in. NPT-F pipe thread.

Size: Height (H): 37.0 in. (940 mm).
Width (W): 27.0 in. (686 mm).
See Figure.

Weight: 7.6 lb (3.4 kg).

Load Rating: 40 lb (18 kg). Designed to support the Nextiva S2800e camera

Minimum Height of Parapet: 16 in. (406 mm).

Minimum Separation Between Brackets: 12.0 in. (305 mm).

Construction: Mount: aluminum.
Brackets: steel.
Hardware: stainless steel.

Finish: White paint.

Shipping Dimensions: (H x W x D): 2.5 x 38 x 30 in.
(63.5 x 965 x 762 mm).

Shipping Weight: 10 lb (4.5 kg).

Shipping Volume: 1.65 ft³ (0.05 m³).

ENVIRONMENTAL

Wind: Withstands winds up to 80 mph.

Storage Temperature: -40 to 150° F (-40 to 65° C).

Storage Humidity: 90% relative, non-condensing.

