

Nextiva S2800e V-UWM Universal Wall Mount

VERINT.

VIDEO INTELLIGENCE SOLUTIONS™



2009 Verint Systems Inc. All Rights Reserved Worldwide.

Unauthorized use, duplication, or modification of this document in whole or in part without the written consent of Verint Systems Inc. is strictly prohibited. By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice. Features listed in this document are subject to change.

Verint Systems Inc. does not warrant, guarantee or make any representation regarding the use or the results of the use of the information, links, tools, and materials in terms of the accuracy, reliability, quality, validity, stability, completeness, currentness, or otherwise of its content or products. The entire risk as to the use, results and performance of information, links, tools and materials provided or referenced herein is assumed by the user. Verint Systems Inc. shall not be liable for damages resulting from the use, misuse or unlawful use of the information, links, tools, and materials contained or referenced herein.

The Verint Systems Inc. products are protected by one or more of the following U.S., European or International Patents: USPN 5,659,768; USPN 5,689,442; USPN 5,790,798; USPN 6,278,978; USPN 6,370,574; USPN 6,404,857; USPN 6,510,220; USPN 6,724,887; USPN 6,751,297; USPN 6,757,361; USPN 6,782,093; USPN 6,952,732; USPN 6,959,078; USPN 6,959,405; USPN 7,047,296; USPN 7,149,788; USPN 7,155,399; USPN 7,203,285; USPN 7,216,162; USPN 7,219,138; USPN 7,254,546; USPN 7,281,173; USPN 7,284,049; USPN 7,325,190; USPN 7,424,715; USPN 7,466,816; USPN 7,478,051; USPN RE40,634; and other provisional rights from one or more of the following Published US Patent Applications: US 11/394,408; US 11/771,499; US 11/396,514; US 11/772,440; US 11/565,943; US 11/565,946; US 11/565,948; US 11/540,739; US 11/540,086; US 11/541,313; US 11/541,252; US 11/540,282; US 11/529,947; US 11/540,785; US 11/540,736; US 11/540,904; US 11/540,353; US 11/608,340; US 11/608,350; US 11/608,358; US 11/567,808; US 11/692,983; US 11/693,933; US 11/693,923; US 11/693,828; US 11/567,852; US 11/608,440; US 12/015,621; US 11/540,322; US 11/924,201; US 11/616,490; US 11/621,134; US 11/752,458; US 11/712,933; US 11/824,980; US 11/729,185; US 11/804,748; US 11/831,260; US 11/395,992; US 11/359,319; US 11/359,195; US 11/359,357; US 10/832,509; US 11/742,733; US 11/831,257; US 11/831,250; US 11/691,530; US 11/479,267; US 11/529,942; US 11/768,349; US 11/540,281; US 10/633,357; US 11/693,899; US 11/479,056; US 11/529,132; US 11/540,320; US 11/037,604; US 11/529,842; US 11/540,171; US 11/478,714; US 11/529,946; US 11/868,656; US 11/776,659; US 11/090,638; US 11/410,004; US 10/771,315; US 10/771,409; US 11/540,900; US 11/528,267; US 12/118,781; and other U.S. and International Patents and Patents Pending.

VERINT, the VERINT logo, ACTIONABLE INTELLIGENCE, POWERING ACTIONABLE INTELLIGENCE, WITNESS ACTIONABLE SOLUTIONS, STAR-GATE, RELIANT, VANTAGE, X-TRACT, NEXTIVA, ULTRA, AUDIOLOG, WITNESS, the WITNESS logo, IMPACT 360, the IMPACT 360 logo, IMPROVE EVERYTHING, EQUALITY, CONTACTSTORE, and CLICK2STAFF are trademarks or registered trademarks of Verint Systems Inc. or its subsidiaries. Other trademarks mentioned are the property of their respective owners.

Product



V-UWM Universal Wall Mount for the Nextiva® S2800e Camera Dome System

- Convenient wall mounting of Nextiva S2800e
- Cable routes through mount for neat appearance
- Easy installation
- Indoor/outdoor application

The V-UWM Universal Wall Mount is designed for the Nextiva S2800e Camera Dome housings. It is a medium-duty wall mount constructed of painted cast aluminum, suitable for indoor or outdoor installations. It has a four hole mounting flange for wall mounting and a cable access hole. The V-UWM has a 1-1/2 inch NPT-F American National Standard Tapered Pipe Thread (NPT). The dome housing is mounted to the V-UWM in this pipe thread.

The hole pattern of the mounting flange is compatible with the V24CMB Corner Mounting Bracket and the V20A Pole Mounting Adapter.

Technical Information

MECHANICAL

Application:	Indoor or outdoor.
Mounting:	Wall or vertical structure.
Mounting Thread:	Standard 1-1/2 inch NPT-F pipe thread.
Dimensions:	See Figure 1. Height (H): 11.6 in. (295 mm). Width (W): 6.3 in. (160 mm). Depth (D): 14.6 in. (371 mm).
Weight:	4.5 lb (2.0 kg).
Construction:	Cast aluminum. Painted white polyurethane.
Shipping Dimensions:	Height: 14.6 in. (371 mm). Width: 7.3 in. (185 mm). Depth: 17.3 in. (440 mm).
Shipping Weight:	5.5 lb (2.6 kg).
Shipping Volume:	1.1 ft ³ (0.03m ³).

ENVIRONMENTAL

Storage Temperature Range:	-40 to 150° F (-40 to 60° C).
Storage Humidity Range:	0 to 90% relative, non-condensing.



VERINT.

VIDEO INTELLIGENCE SOLUTIONS™

